

## Technical Specifications **GF-8** Crane System

<b>Version</b>	<b>Reach</b>	<b>Max. Height Euro-adapter</b>	<b>Max. Payload</b>	<b>Counterweight at Max. Payload</b>	<b>Crane Weight <i>no dolly</i></b>
1	253cm / 8' 3"	331cm / 10' 10"	250 kg / 550lbs	276kg / 607lbs	184kg / 404lbs
2	350cm / 11' 5"	412cm / 13' 5"	250 kg / 550lbs	456kg / 1003lbs	209kg / 459lbs
3	401cm / 13' 1"	453cm / 14' 10"	216kg / 475lbs	480kg / 1056lbs	215kg / 473lbs
4	498cm / 16' 4"	534cm / 17' 6"	150kg / 330lbs	480kg / 1056lbs	227kg / 499lbs
5	549cm / 18'	576cm / 18' 10"	128 kg / 281lbs	480kg / 1056lbs	234kg / 514lbs
6	663cm / 21' 8"	675cm / 22' 1"	80kg / 176lbs	420kg / 924lbs	237kg / 521lbs
7	713cm / 23' 4"	716cm / 23' 5"	80kg / 176lbs	476kg / 1047lbs	243kg / 534lbs
8	810cm / 26' 6"	798cm / 26' 2"	50kg / 110lbs	480kg / 1056lbs	257kg / 565lbs
<b>Version</b>	<b>Reach</b>	<b>Rear Extension</b>	<b>Total Bucket L.</b>	<b>Max. Payload</b>	<b>Front Extension</b>
3A	15'	1 x 1'5"	55"	60kg / 132lbs	2 x 5' + 1 x 2'5"
3A	13'6"	1 x 1'5"	55"	80kg / 180lbs	2 x 5'
5A	18'5"	1 x 2'5"	69"	60kg / 132lbs	3 x 5'
5A	17'6"	1 x 2'5"	69"	80kg / 180lbs	2 x 5' + 1 x 4'
5A 36mm	13'1"	1 x 2'5"	69"	144kg / 320lbs	2 x 5'
5A 16mm	9'7"	1 x 2'5"	69"	220kg / 480lbs	1 x 5' + 1' x 1'5"
5B	22'6"	1 x 3'	78"	60kg / 132lbs	3 x 5' + 1 x 4'
5B	21'	1 x 3'	78"	80kg / 180lbs	3 x 5' + 1 x 2.5"
5B 16mm	15'7"	1 x 3'	78"	123kg / 270lbs	2 x 5' + 1 x 2.5"
5B 35mm	14'5"	1 x 3'	78"	140kg / 310lbs	2 x 5' + 1 x 1.5"
5C 16mm	12'2"	1 x 3'	78"	220kg / 480lbs	1 x 5' + 2.5" + 1.5"
5C 35mm	10'10"	1 x 3'	78"	245kg / 540lbs	1 x 5' + 1 x 2.5"

The length of the rear end as measured from the pivot point to the out side of the weight bucket 220cm/7'2"

Maximum amount of counterweight in bucket is 30 x 16kg = 480 kg / 1056lbs | All versions are with bucket extension 127cm / 4' 2" | Base 4'2"x 38" center pivot point with 1 riser 61" | More spec's available when using odd size sections on front or back 40cm/1'5" \* 75cm/ 2'5" \* 100cm / 3' Dolly weight = 80 kg / 176lbs